



PROJECT:	MODEL:	QUANTITY:	ITEM NO:

# ENCLOSED TRAY CABINETS

For 12" Wide Patient Trays

"ETC PATIENT TRAY SERIES 3"

**NO HEAT**

**NON-INSULATED**

- Non-Heated
- Non-Insulated
- Adjustable Tray Slides

**FITS PATIENT TRAYS:**

- 12" x 16"
- 12" x 19"
- 12" x 20"
- 12" x 22"



ETC-1250-28



ETC-1240-10  
Shown with Beverage Urn Angles optional accessory.

*Rugged patient tray transports in sanitary stainless steel - Easy to maintain and non-electrical!*

FWE "ETC-1240/1250 Series" patient trays transports are fully enclosed, heavy-duty cabinets that let you serve hot and cold foods together, using pellet systems, insulated, or disposable containers.

Our unique upright/tray slide arrangement accommodates any 12" wide tray, in a variety of lengths. These non-heated cabinets are never "out of order", since they use no outside power source. Minimize the number of staff needed for meal prep/delivery, and save on budget, while still delivering hot, appetizing meals to your patient population.

"ETC-1240/1250 Series" cabinets are available with single or double doors, and in low or high profile models, accommodating from 10 to 36 trays. All have the high quality features and construction that have made FWE the "Choice of the Professionals."

- ◇ All stainless steel
- ◇ All welded construction - no rivets
- ◇ Tubular stainless steel welded base frame
- ◇ Full extension bumper
- ◇ Heavy-duty polyurethane casters
- ◇ Heavy-duty lift-off hinges
- ◇ Positive close door latch
- ◇ Heavy-duty tubular push bar handles
- ◇ Doors lie flush when open
- ◇ Insulated door(s)
- ◇ Pitched center drain
- ◇ Removable and adjustable tray slides
- ◇ Two year limited warranty



PROJECT:


MODEL:

QUANTITY:

ITEM NO:



# SPECIFICATIONS:

## ENCLOSED TRAY CABINETS

Series 3  
Patient Trays

### Spacing the Tray Slides to meet your capacities:

Tray Slides can be positioned at a choice of .75" increments for greater flexibility.



Side View of ETC-1240-10

**FWE Products are used by major companies world-wide. We can modify, design, or custom build equipment to fit your special requirements.**

MODEL NUMBER	TRAY CAPACITIES FOR 12" WIDE TRAYS						OVERALL EXTERIOR DIMENSIONS IN. (mm)			Consult Factory for SHIPPING CLASS			
	NUMBER OF TRAYS AT SPACINGS OF:						HIGH "H"	DEEP "D"	WIDE "W"	NO. OF DOORS	CASTER SIZE	SHIP WT. LBS. (KG)	CUBIC FEET (m <sup>3</sup> )
	3.0"	3.75"	4.5"	5.25" <sup>[A]</sup>	6.0"	6.75"							
ETC-1240-10	16	14	12	10	8	6	41" (1041)	26.75" (679)	35.75" (908)	1	6"	140 (63)	22.69 (.64)
ETC-1250-14	20	18	16	14	12	10	49.5" (1257)	26.75" (679)	35.75" (908)	1	6"	200 (90)	27.39 (.78)
ETC-1240-20	32	28	24	20	16	12	41" (1041)	26.75" (679)	65" (1651)	2	6"	300 (135)	41.26 (1.17)
ETC-1250-28	40	36	32	28	24	20	49.5" (1257)	26.75" (679)	65" (1651)	2	6"	350 (158)	49.81 (1.41)

[A] Model numbers are based on capacities @ spacings of 5.25". Tray slides can be positioned at a choice of .75" increments.

See-thru Lexan Door [add "L"] displays cabinet contents for easy monitoring. Pass-thru Door and Dutch Doors are available on some model numbers. Consult Factory.

### CONSTRUCTION.

Heliarc welded, single unit construction of 18-gauge stainless steel. Welded tubular base frame shall be 1" square, heavy gauge stainless steel tubing, with 10-gauge stainless steel reinforcing plates at corners and fittings.

**PUSH BAR HANDLES.** Heavy-duty, 1" diameter tubular stainless steel push handles: One (1) on single door units mounted on side of unit, two (2) on multi-door units mounted on each end of unit. Mountings reinforced with stainless steel channel.

**BUMPER.** Solid 1.5" wide continuous wraparound aluminum channel, bolted to frame, with snap-in, non-marking replaceable vinyl cushion. Full perimeter bumper extends beyond doors, handles, etc., for added protection. Shall be continuous, with corner cut-outs to facilitate cleaning.

**DOORS AND LATCHES.** Flush mounted, stainless steel insulated doors. When opened doors lie flush against side of unit or another door to keep work aisles unobstructed. Each door shall have two (2) heavy-duty, lift-off, 12-gauge stainless steel hinges. Each door shall be equipped with a positive closing, flush-in-door, stainless steel paddle latch. The hinge and latch mountings are reinforced with stainless steel backing plates.

**CASTERS.** Maintenance free polyurethane tire casters in a configuration of two (2) rigid and two (2) swivel with brake. Casters shall have a reinforced yoke mounted to 10-gauge caster plate. The caster mounting plate shall be secured to a 10-gauge stainless steel reinforcing stress plate via welded in place stainless steel studs. The reinforcing stress plates shall be welded to the heavy gauge tubular frame of the unit.

**TRAY SLIDES.** Welded rod-style tray slides are nickel plated for greater durability and sanitation. Fully adjustable / removable and designed to give secure bottom tray support. Removable stainless steel uprights shall be punched on .75" spacing for easy tray/pan adjustment, and shall easily lift off heavy-duty, stainless steel brackets without the use of tools.

**PITCHED DRAIN.** Cabinet shall have a pitched center drain to facilitate thorough cleaning of interior.

### Optional Accessories:

- See-thru Lexan door
- Key locking door latch
- Padlocking transport latch
- Door swing configuration
- Security packages
- All swivel or larger casters
- Door edge trim
- Cold plate cartridge
- Menu card holder
- Top guard rail (3 or 4 sided)
- Beverage urn angles
- Extra tray slides
- Fixed-in-place tray slides



### Food Warming Equipment Company, Inc.

P.O. Box 1001  
Crystal Lake, IL 60039 USA  
800-222-4393; 815-459-7500  
Fax: 815-459-7989

Manufacturing Facilities:  
7900 S. Route 31  
Crystal Lake, IL 60014 USA  
www.FWE.com sales@fweco.net

FWE products may be covered under one or more of the following U.S. patents: 288,299;238,300;3,952,609;4,192,991.

All specifications subject to change without notice. © 11H Food Warming Equipment Company, Inc.