

Job: _____

Item No: _____

CA66-RR10-PT-6PS

Aluminum Meal Delivery Cart

Features:

- Enclosed aluminum cabinet with solid pass through doors that open 270 degrees
- Drain holes in base for easier internal cleaning
- Perimeter bumper for fixture & wall protection
- 1" x 5" tray supports on removable inner panels
- Tray supports on 5 1/2" centers

Tray Sizes Supported:

- 14" x 18"
- 15" x 20"
- 15 1/4" x 20 1/2"

Options:

- 5" "C" channel tray supports on removable inner panels
- Caster options available





CA66-RR10-PT-6PS
Aluminum Meal Delivery Cart

| Lockwood Model No. | Pan | | | Exterior Dimensions | | | | Weight |
|--------------------|---------|----------|----|---------------------|-------|---------|-----|--------|
| | Angles | Capacity | | Width | Depth | Height | | |
| CA66-RR10-PT-6PS | 10 pair | 20 | IN | 29 | 39 | 66.0125 | LBS | 166 |
| | | | CM | 73.66 | 99.06 | 167.97 | KG | 75.3 |

Cabinet Specifications:

- Top: One piece .080" aluminum; welded to frame
- Side panels: Formed .080" aluminum; welded to frame
- Frame: .125" wall, 1.5" square tube

Lockwood reserves the right to change materials and specifications without notice.

Base Specifications:

- One piece .125" aluminum; formed construction
- Casters: (2) 6" x 2" Performa quiet tread swivel with precision bearings and brakes; (2) 6"x2" rigid Performa quiet casters; load capacity 675 lbs each

Door Specifications:

- Frame: 7/8" x 1 3/4" extruded aluminum screwed and welded together
- Panel: .063" solid aluminum sheet, fitted into door frame
- Latch: Magnetic type latch handle screwed to door frame
- Hinges: 4" stainless steel - opens 270°
- Gasket: Perimeter; fitted into frame extrusion, flexible PVC rubber

Pan Support Specifications:

- Extruded .090" aluminum
- Welded to removable inner panels